

## SUBSTITUTE SPECIFICATION WITH CHANGES MARKED

**Apparatus for the production of caps**

This invention relates to an apparatus for the production of caps, for example associatable with containers such as bottles for drinks, containers for detergents and receptacles in general.

Caps are known that are associated with different types of container.

Such caps can be obtained by forming through compression or through injection moulding.

The caps disclosed above are provided with a seal ring which, when the caps are first opened, remains attached to a container in such a way as to clearly show to a user whether the container has already been opened.

In order that the seal ring may be easily separable from the cap, the zone interposed between the seal ring and the cap is provided with a nominal indented cutting line.

The seal ring is provided with fixing promoting devices, for example having the form of flaps, suitable for interacting with a stop element obtained at a delivery port of the container and suitable for preventing the detachment of the seal ring from the container during the first opening of the latter.

Apparatuses for the manufacture of caps are known that are arranged to receive on operating rotating elements a cap obtained by compression forming or by injection moulding and comprising a bottom wall, a side wall that defines a side mantle of the cap, a seal ring and fixing promoting devices, such fixing promoting devices comprising appendages that are projected from the side wall in a direction opposite the bottom wall.

Such apparatuses comprise a first turntable with which a folding unit ~~folding means is~~ is associated arranged to fold

the aforementioned appendages towards the inside of the caps, namely in the direction of the aforementioned base wall.

The apparatuses furthermore comprise a second turntable with which a cutting unit is associated that is ~~are associated~~  
 5 ~~cutting means~~ arranged to make an incision on the aforementioned side wall in such a way as to define a nominal cutting line interposed between the seal ring and the mantle of the cap.

Alternatively, the cutting unit ~~means~~ can be associated with a first turntable and the folding units ~~means~~ can be associated  
 10 with a second turntable.

The ~~cutting means~~ unit comprises an ~~incision-etching~~ knife, arranged outside the cap, against which the aforementioned side wall is made to rotate by means of a suitable cap moving  
 15 ~~means~~ unit.

The ~~incision-etching~~ knife comprises a blade shaped in such a way as to have a series of teeth to make incisions in the side wall of the cap that pass through the side wall, between which zones without incisions are interposed, which constitute  
 20 bridge elements suitable for being broken when the cap is first opened.

Alternatively, the ~~incision-etching~~ knife may comprise a blade with a continuous cut that is suitable for interacting with caps that have a side wall with a variable thickness.

25 In this case, the through incisions are made in the zones of the side wall that have less thickness, whilst the bridge elements are defined at the zones of the side wall that have greater thickness.

The apparatuses disclosed above furthermore comprise a  
 30 transport device interposed between the first turntable and the second turntable and suitable for picking up from the first turntable caps provided with already folded flaps to transfer them to the second turntable.

The transport device comprises a conveyor along which the caps are advanced in a substantially straight direction.

One drawback connected with the use of the transport device disclosed above consists of the fact that it implies a transient, in which a cap that comes from a rotational movement - given by the first turntable - takes on straight movement, and a further transient, in which the straight movement of the cap associated with the conveyor is transformed into a rotational movement at the moment of transfer onto the second turntable.

On the first turntable and on the second turntable the caps are received in respective seats that are separated from one another by an angle of a preset degree.

This means that on the first turntable and on the second turntable, the caps are distanced from one another and the movement of each of them is synchronized with the movement of the remaining caps.

On the other hand, in the conveyor the caps substantially move behind one another without the movement of each one of them being in phase with the movement of the others.

At an input region of the second turntable it is therefore necessary to distance the caps from one another to enable the latter to be correctly loaded onto the second turntable.

For this purpose, conveyors must be provided having a length that is such as to enable the caps to be distanced from one another and to synchronize the movements of the latter.

The known apparatuses comprise conveyors having lengths up to about three metres.

As a result, the apparatuses disclosed above have to be necessarily assembled in very spacious environments and do not allow optimum use of the spaces of a building inside which they have to be installed.

European patent application EP-A-1243520 discloses an apparatus for the production of caps comprising a sole

operating turntable with which both a folding means-unit and a cutting means-unit are associated.

The apparatus furthermore comprises a first transfer turntable suitable for supplying the operating turntable and a second  
5 transfer turntable suitable for receiving the finished caps.

In this apparatus the folding means-unit and the cutting means-unit are arranged in positions that are angularly subsequent and one after the other they interact with the caps.

As the apparatus disclosed above is provided with a spindle  
10 that must be adapted both to the fold and to the cut, for certain types of caps such a spindle may not be able to satisfactorily perform both functions (folding and cutting).

The folding means-unit disclosed in EP-A-1243520 comprises a ring provided with a tapered end suitable for being inserted  
15 inside the caps.

A further drawback of the apparatus disclosed above consists of the fact that the aforementioned ring, being projectingly supported on corresponding support elements, tends to flex.

As a result, the caps, whilst they are associated with the  
20 operating turntable, must be subjected to a plurality of operations that are rather close in time, such operations being furthermore performed in zones of the apparatus that are at a small distance from one another.

In particular, in addition to the folding and cutting  
25 operations, there must be provided an operation of insertion of the caps inside the seats with which the operating turntable is provided, and an operation of pickup of the caps from the operating turntable.

As a result, further operations cannot be provided, connected  
30 for example to quality control and finishing, whilst the caps are associated with the operating turntable.

A further drawback of the apparatuses disclosed above consists  
of the fact that the blade of the incision-etching knife with

which the cutting ~~means-unit~~ is provided is subjected to significant wear.

It is therefore necessary to manually position the ~~incision~~ etching knife by moving its blade in the direction of the zone of contact with the caps, in such a way as to offset a shortening of the blade due to the aforementioned wear.

Manual positioning occurs by means of the use of a split nut, provided with a micrometric screw, that is coupled with a toolholder that supports the ~~incision~~ etching knife.

The aforementioned split nut is manually actuatable by means of a handwheel.

As a result, to carry out the adjustment of the position of the blade, it is necessary to stop the apparatus and perform complex adjusting operations in order not to subject the aforementioned micrometric screw to the loads that are exerted during cutting.

To discharge the screw from the aforementioned mechanical stress, a clamp lock of the ~~incision~~ etching knife may be provided, which however significantly increases the complexity of the apparatus, and the cost of thereof.

Apparatuses of the known type are equipped with a folding means-unit provided with punches that exert a pulse action on the fixing promoting ~~means-unit~~ in a substantially axial direction to the inside of the caps.

A further drawback of the known apparatuses therefore consists of the risk of determining on the caps plastic deformation that is often of an unacceptable amount.

One object of the invention is to improve the apparatuses for the production of caps.

A further object of the invention is to provide an apparatus for the production of caps that enables a plurality of operations to be performed on the aforementioned caps.

A further object of the invention is to obtain an apparatus for the production of caps from which the aforementioned caps can be evacuated according to any direction of advance.

5 | A yet further object is to obtain an apparatus for the production of caps in which the cutting ~~means~~unit can be positioned with extreme precision and without necessarily interrupting the work cycle of the apparatus.

10 | A yet further object of the invention is to obtain an apparatus for the production of caps provided with a positioning means device for positioning ~~of~~ the cutting ~~means~~unit that, during operation, ~~are~~is substantially not subjected to mechanical stress.

15 | A yet further object of the invention is to obtain an apparatus for the production of caps provided with a folding means~~unit~~ shaped in such a way as not to cause plastic deformations of the caps.

20 | In a first aspect of the invention, an apparatus is provided for the production of caps, comprising a first operating turntable means device associated with a first operating means arrangement and a further operating turntable means device associated with a further operating means arrangement, ~~characterised in that wherein~~ between said first operating turntable ~~means device~~ and said further operating turntable ~~means device~~ there is interposed a transfer transferring  
25 | turntable ~~means device~~ such as to translate said caps between said first operating turntable ~~means device~~ and said further operating turntable ~~means device~~.

30 | In one embodiment, the first operating ~~means arrangement~~ comprises a folding means arrangement, arranged to fold a fixing promotion promoting means arrangement with which said caps are provided, and the further operating ~~means arrangement~~ comprises a cutting means arrangement, arranged to make nominal cutting line means in a side wall of the caps.

In another embodiment, the first operating ~~arrangement~~means comprises a cutting ~~means~~ arrangement, whereas the further operating ~~means~~ arrangement comprises a folding ~~means~~ arrangement.

5 In a further embodiment, the apparatus furthermore comprises a further ~~transfer~~ transferring turntable ~~means~~ device such as to pick up the caps from the further operating turntable ~~means~~ device.

Owing to this aspect of the invention it is possible to obtain  
10 an apparatus for the production of caps that is provided with limited overall dimensions inasmuch as the ~~transfer~~ transferring turntable ~~means~~ device is provided with rather a compact shape.

The presence of the ~~transfer~~ transferring turntable ~~means~~ device  
15 device enables the installation of large conveyor ~~means~~ device to be avoided between the first operating turntable ~~means~~ device and the further operating turntable ~~means~~ device.

As the rotation speed of the ~~transfer~~ transferring turntable ~~means~~ device is synchronized with that of the first operating  
20 turntable ~~means~~ device and of the second operating turntable ~~means~~ device it is possible to obtain an effective and simple movement of the caps.

Furthermore, owing to the presence of a further ~~transfer~~ transferring turntable ~~means~~ device, the caps can be 'evacuated'  
25 from the apparatus according to any direction of advance .

Providing a rotating device specifically intended for unloading the caps from the apparatus in fact enables  
30 selecting the angular position of the further ~~transfer~~ transferring turntable ~~means~~ device at which to provide a pickup line.

As no further operation has to be performed whilst the caps are associated with the further ~~transfer~~ transferring turntable ~~means~~ device, the aforementioned pickup line can be

arranged substantially in any position in relation to the second ~~transfer~~-transferring turntable ~~means~~device.

This enables the apparatus to be positioned inside an environment in such a way as to optimize the space delimited  
5 by the aforementioned environment.

This is made possible by the fact that the apparatus can have an extent and a shape such as to adapt to any structural constraints present in the aforementioned environment.

In a second aspect of the invention, an apparatus is provided  
10 for the production of caps, comprising a first operating turntable means-device associated with a first operating means arrangement and a further operating turntable means-device associated with a further operating means arrangement,  
~~characterised in that~~wherein between said first operating  
15 arrangement means and said second-further operating arrangement means-a monitoring means-device is interposed arranged to monitor said caps.

In one embodiment, the first operating arrangement means comprises a folding means-arrangement arranged to fold a  
20 fixing ~~promotion~~-promoting means-arrangement with which said caps are equipped, and said second-further operating arrangement means comprises a cutting means-arrangement arranged to make a nominal cutting line means-in a side wall of said caps.

In one embodiment, the apparatus furthermore comprises,  
25 downstream of the monitoring ~~means~~device, a pickup means arrangement arranged to pick up from the apparatus caps that have been deemed not to conform to a preset quality standard following an examination conducted by the aforementioned  
30 monitoring meansdevice.

In another embodiment, the monitoring ~~means~~-device comprises cameras.

Owing to this aspect of the invention, defective caps can be rejected before being subjected to cutting operations.



This makes it possible to prevent caps from damaging the cutting ~~means~~arrangement.

In one embodiment, the monitoring ~~means~~device is associated with a ~~transfer~~transferring turntable ~~means~~device interposed  
 5 between a first operating turntable ~~means~~device with which the folding arrangement is associated ~~the folding means~~ and a further operating turntable ~~means~~device with which the cutting ~~means~~arrangement is associated.

Providing the aforementioned ~~transfer~~transferring turntable  
 10 ~~means~~device enables the apparatus according to the invention to be equipped with further operating devices - such as monitoring ~~means~~devices or the like - suitable for performing on the caps additional operations to the folding and cutting operations.

15 This enables a considerable advantage to be achieved compared with the prior art, inasmuch as such further operating devices are difficult to install on apparatuses made according to the teachings of EP-A-1243520.

In a third aspect of the invention a device is provided for  
 20 positioning a tool in relation to an object to be processed, comprising a toolholder ~~means~~element suitable for bearing said tool and an adjustable member operationally associatable with said toolholder ~~means~~element, ~~characterised in that~~  
 25 ~~wherein it furthermore comprises an~~ abutting stop member is furthermore comprised, said abutting member being suitable for tightening said toolholder ~~means~~element against said adjustable member.

In one embodiment, the adjustable member comprises a block  
 30 actuated to slide by an adjusting ~~means~~arrangement and provided with a tilted face suitable for interacting with a correspondingly tilted active surface of the toolholder ~~means~~element.

In another embodiment, the ~~stop~~abutting member comprises a further tilted face suitable for interacting with a further

correspondingly tilted active surface opposite the  
aforementioned active surface of the toolholder ~~means~~element.

Owing to this aspect of the invention, it is possible to  
obtain a device for positioning a tool, provided with an  
5 | ~~adjusting means—arrangement~~ arranged to move the adjustable  
member, which adjusting member is not substantially subjected  
to mechanical stress during operation of the apparatus.

In particular, it is possible to obtain an apparatus for the  
production of caps wherein the distance of the cutting ~~means~~  
10 | arrangement from the caps to be cut can be adjusted to offset  
shortening due to cutting ~~means—arrangement~~ wear.

In a fourth aspect of the invention, an apparatus is provided  
for the production of caps comprising a chamber seat—means  
element isolated from an external environment and arranged to  
15 | receive said caps to enable said caps to be subjected to  
controlled treatment.

In one embodiment, with the chamber ~~means—element~~ an adjusting  
~~means—arrangement~~ is associated arranged to adjust the  
temperature inside the chamber ~~means~~element.

20 | In another embodiment with the chamber ~~means—element~~ an  
~~irradiation—irradiating~~ ~~means—arrangement~~ is associated  
arranged to irradiate the caps.

In a further embodiment, with the chamber ~~means—element~~ a  
~~cleaner—cleaning~~ ~~means—arrangement~~ is associated arranged to  
25 | perform cap cleaning operations.

In a yet further embodiment, the chamber ~~seat—means~~element is  
associated with a turntable ~~means—device~~ arranged to transfer  
the caps.

Owing to this aspect of the invention, it is possible to  
30 | obtain an apparatus in which the caps can be subjected to  
treatment in a controlled environment.

In a fifth aspect of the invention, an apparatus is provided  
for the production of caps, comprising a cutting ~~means~~  
arrangement arranged to make on said caps a nominal cutting

line ~~means~~, ~~characterised in that~~ wherein ~~it furthermore~~  
~~comprises a sensor~~ sensing means ~~arrangement~~ is furthermore  
 comprised, said sensing arrangement being operationally  
 associated with said cutting means arrangement in such a way  
 5 as to monitor the positioning of said cutting means  
arrangement in relation to said caps.

In one embodiment, the ~~sensor~~ sensing means ~~arrangement~~  
 comprises a position sensor ~~sensing means~~ device arranged to  
 detect thermal dilations of an incision etching knife ~~means~~ of  
 10 the cutting means arrangement.

In another embodiment, the ~~sensor~~ sensing means ~~arrangement~~  
 comprises a temperature sensor ~~sensing means~~ device arranged  
 to detect the temperature of said caps.

In a further embodiment, the ~~sensor~~ sensing means ~~arrangement~~  
 15 comprises a colour sensor ~~sensing means~~ device arranged to  
 detect the colour of said caps.

In a sixth aspect of the invention, an apparatus is provided  
 for the production of caps, comprising a folding means  
arrangement arranged to fold a fixing ~~promotion~~ promoting  
 20 ~~means arrangement~~ inside said caps, ~~characterised in~~  
~~that~~ wherein said folding means arrangement comprises an  
articulated folding means device provided with an operating  
 zone movable between an inactive position, in which said  
 operating zone is positioned outside said caps, and a work  
 25 position, in which said operating zone is received inside said  
 caps in such a way as to fold said fixing ~~promotion~~ promoting  
~~means arrangement~~ inside said caps.

Owing to this aspect of the invention, it is possible to  
 obtain an apparatus for the production of caps in which the  
 30 risks of damage to the caps during folding operations of the  
fixing ~~promotion~~ promoting means arrangement are noticeably  
 limited or are even completely eliminated.

In a seventh aspect of the invention, an apparatus is provided  
 for the production of caps, comprising a folding means

arrangement arranged to fold a fixing ~~promoting~~ promoting  
~~means~~ arrangement with which said caps are provided and a  
cutting ~~means~~ arrangement arranged to make a nominal cutting  
line ~~means~~ in a side wall of said caps, characterised  
5 ~~in wherein~~ that said cutting ~~means~~ arrangement is coaxial to  
said folding ~~means~~ arrangement and is arranged outside said  
folding ~~means~~ arrangement.

The invention can be better understood and implemented with  
reference to the attached drawings that show a non-limiting  
10 embodiment by way of example, in which:

Figure 1 is a plan view of an apparatus for the production of  
caps;

Figure 2 is a plan view of a ~~transfer~~ transferring turntable  
~~means~~ device of the apparatus in Figure 1;

15 Figure 3 is a partially sectioned side view of an operating  
turntable ~~means~~ device of the apparatus in Figure 1 with which  
a cutting ~~means~~ arrangement is associated, shown in an  
operating configuration, and a positioning ~~means~~ arrangement  
of the aforementioned cutting ~~means~~ arrangement;

20 Figure 4 is a view like the one in Figure 3, showing the  
cutting ~~means~~ arrangement in a rest configuration;

Figure 5 is a view like the one in Figure 3, showing a  
monitoring ~~means~~ device associated with the cutting  
~~means~~ arrangement;

25 Figure 6 is a plan view of the apparatus in Figure 5;

Figure 7 is a view like the one in Figure 3 showing the  
cutting ~~means~~ arrangement, shown in a rest configuration, and a  
positioning ~~means~~ arrangement of the cutting ~~means~~ arrangement  
made according to one version;

30 Figure 8 is a view like the one in Figure 3, showing the  
cutting ~~means~~ arrangement in a rest configuration;

Figure 9 is a plan view of a support element of the cutting  
~~means~~ arrangement with which the positioning ~~means~~ arrangement  
shown in Figure 7 is provided;

Figure 10 is a view from behind of the positioning ~~means~~  
arrangement arranged in a locking configuration, when the  
cutting ~~means~~arrangement is in the operating configuration  
shown in Figure 8;

5 Figure 11 is a detail of Figure 7;

Figure 12 is a plan view showing the cutting ~~means~~arrangement  
in the operating configuration in Figure 8;

Figure 13 is a side view of a pressurized air recovery device  
associated with an apparatus according to the invention;

10 Figure 14 is a plan view of the device in Figure 13;

Figure 15 is a section taken along a transverse plane of a  
folding ~~means~~arrangement of the apparatus according to the  
invention;

Figure 16 is a section taken along a transverse plane of one  
15 ~~preferred~~ embodiment of the ~~transfer~~transferring turntable  
~~means~~device;

Figure 17 is a view like the one in Figure 6 showing a ~~sensor~~  
sensing ~~means~~arrangement suitable for detecting the position  
of the cutting ~~means~~arrangement;

20 Figure 18 is a partial section taken along a transverse plane  
of one embodiment of the apparatus for the production of caps  
according to the invention;

Figure 19 is a partially sectioned front view showing the  
apparatus in Figure 18 in a phase preceding execution of  
25 folding of the fixing promoting ~~means~~arrangement with which  
the caps are provided;

Figure 20 is a partially sectioned front view of the apparatus  
in Figure 18 showing a fixing promoting ~~means~~arrangement  
folded inside a cap;

30 Figure 21 is a section taken along the plane XXI-XXI in Figure  
19.

With reference to Figures 1 and 2, an apparatus 1 is shown for  
the production of caps 2 suitable for being associated with  
containers in general.

The caps 2 can be made by compression forming or by injection moulding, of a plastic material.

The caps 2 comprise a base wall suitable for closing an opening of the aforementioned containers and a side wall  
5 suitable for interacting with a neck of the containers.

In the side wall, a mantle can be identified, which may be internally provided with a thread suitable for engaging in a corresponding thread obtained in the aforementioned neck, with  
| a seal ring that acts as an opening indicator means ~~element~~.

10 Between the mantle and the seal ring there is provided a nominal cutting line consisting of incisions passing through the side wall, interrupted by non-cut zones that constitute bridge elements suitable for being fractured in the course of the first opening of the caps 2.

15 | With the seal ring a fixing promoting means ~~arrangement~~ is connected suitable for preventing the seal ring from getting detached from the corresponding container during said first  
| opening. The fixing promoting ~~means~~ arrangement comprises a plurality of flaps 54 (Figure 15), or of a continuous ring 106  
20 (Figures 18 and 19), that interact with a stop obtained on the neck of the container.

The flaps 54, at the outlet of a mould in which the caps 2 have been formed, take on a first position in which they are turned towards the exterior of the caps 2, or are  
25 substantially parallel to the base wall of the caps 2.

In other words, the flaps 54, at the outlet of the mould, take on a position that is different from a further position they have to take on once they have been applied to the neck of a container.

30 Before the caps 2 have been associated with the corresponding containers, the flaps 54 are taken to the further position, in which they are turned towards the inside of the caps 2.

The apparatus 1 comprises a first operating turntable 3 with  
| which is associated a folding means ~~arrangement~~ 52 (Figure 15)

arranged to fold the flaps 54, transferring them from the aforementioned first position to the aforementioned further position.

5 The apparatus 1 comprises a conveying device 8 arranged for supplying the first operating turntable 3.

The conveying device 8 comprises a pneumatic conveyor inside which the caps 2 are advanced, substantially one in contact with the other, by means of pressurized air.

10 The apparatus 1 furthermore comprises a second operating turntable 4 with which is associated a cutting means arrangement 5 arranged to make the nominal cutting line in the side wall of each of the caps 2.

15 The apparatus 1 is furthermore provided with a ~~transfer~~ transferring turntable 6 interposed between the first operating turntable 3 and the second operating turntable 4 and suitable for transferring the caps 2 in the course of processing from the first operating turntable 3 to the second operating turntable 4.

20 The ~~transfer~~ transferring turntable 6 enables an extremely compact apparatus to be obtained, inasmuch, unlike what happens in the known apparatuses of the prior art, no linear connection channels are provided interposed between the first operating turntable 3 and the second operating turntable 4.

25 The apparatus 1 is furthermore provided with a further ~~transfer~~ transferring turntable 7, suitable for receiving the caps 2 from the second operating turntable 4 to deliver them to a further conveying device 9, comprising a driven conveyor belt 10, that advances them towards ~~collection~~ collecting devices ~~means~~.

30 The further ~~transfer~~ transferring turntable 7 enables the caps 2 to be evacuated from the apparatus 1 in such a way that they advance on the conveyor belt 10, being separated from one another by a preset distance.

This enables auxiliary devices 13 to be provided, associated with the conveyor belt 10, suitable for conducting caps 2 monitoring, finishing or pickup operations.

The auxiliary devices 13 may for example comprise cameras 11  
5 | suitable for checking for the presence of any defects, or  
| ~~removal-removing means-devices~~ 12 arranged to reject caps 2 that have been found to be defective.

The presence of the further ~~transfer~~-transferring turntable 7  
10 | enables the further conveying device 9 to be directed in any  
| direction in relation to the apparatus 1.

As shown in Figure 1, in fact the further conveying device 9 can be arranged in position X, indicated by a continuous line, or in the further positions Y, or Z, indicated with a broken line, or in any other position.

15 | In this way, the production line of the caps 2 may overall  
| have any direction in such a way as to optimize the exploitation of the space of environments inside which it is installed.

20 | Providing a further ~~transfer~~-transferring turntable 7  
| specifically dedicated to the evacuation of the caps 2 in fact enables the further conveying device 9 to be associated with any point of the latter.

25 | In other words, the caps 2 may perform on the further ~~transfer~~-transferring turntable 7 an angular shift of the desired  
| amount, it being possible to select this amount for the purpose of positioning at will the point of connection of the  
| further ~~transfer~~-transferring turntable 7 with the further conveyor 9 and to direct the latter according to a desired direction.

30 | This was not possible in the known apparatuses of the prior art which were not provided with an unloading turntable. In the aforementioned apparatuses in fact the unloading of the caps could occur only after overcoming a minimum value of the angular stroke of the operating turntable, this value being



determined by the number and type of the operations that have to be conducted whilst the caps are on the aforementioned operating turntable.

In the aforementioned apparatuses, the above operations  
 5 require a rotation corresponding to an angle of about  $300^\circ$ , and as a result the unloading of the finished caps 2 must occur in the course of a further rotation corresponding to an angle degree limited to only  $60^\circ$  approximately.

In order to better understand the operation of the apparatus  
 10 1, in Figure 1, the arrow F shows the direction of rotation of the first operating turntable 3, the arrow F1 shows the direction of rotation of the ~~transfer~~-transferring turntable 6, the arrow F2 shows the direction of rotation of the second operating turntable 4 and the arrow F3 shows the direction of  
 15 rotation of the further ~~transfer~~-transferring turntable 7.

With reference to Figure 2, the ~~transfer~~-transferring turntable 6 comprises a rotating table 14 provided with seats  
 15 15 angularly distanced from one another and suitable for each receiving a cap 2.

20 The ~~transfer~~-transferring turntable 6 furthermore comprises an inlet guide 16, suitable for promoting the insertion of the caps 2 inside the seats 15, and an outlet guide 17 suitable for promoting the evacuation of the caps 2 from the rotating table 14.

25 The ~~transfer~~-transferring turntable 6 furthermore comprises an intermediate guide 18 that cooperates with the seats 15 to keep the caps 2 in the correct position during actuation of the rotating table 14.

30 With the ~~transfer~~-transferring turntable 6 a camera 19 is associated that is suitable for monitoring the caps 2 that are conveyed from the rotating table 14 in order to identify any faults in the latter.

An expulsion device 20 can also be provided comprising an element generating a jet of pressurized air 21 arranged to

reject the caps 2 that have been recognized as defective by the camera 19.

With the ~~transfer~~-transferring turntable 6 a cutting device 37 is furthermore associated that is suitable for removing from an external zone of the bottom wall of the caps 2 appendages of the casting feedhead, in the case of caps 2 obtained by injection moulding.

As the aforementioned nominal cutting line is obtained by making the caps 2 roll on the cutting ~~means~~-arrangement 5, the aforementioned appendages may constitute unevenness that hinder correct rolling.

As a result, if the appendages are not removed, the nominal cutting line can define an elliptic length rather than a circumference and the cap 2 on which it has been made must therefore be rejected.

The first operating turntable 3, the second operating turntable 4, the ~~transfer~~-transferring turntable 6 and the further ~~transfer~~-transferring turntable 7 may have diameters that are different from one another and as a result on each of them a different number of seats 15 may be obtained.

With reference to Figures 3 and 4 there ~~are~~-is shown a cutting ~~means~~-arrangement 5 comprising a positioning device 22 suitable for positioning an ~~incision~~-etching knife 23 in relation to a cap 2 to be cut.

The positioning device 22 comprises a toolholder block 24 arranged to support the ~~incision~~-etching knife 23, the toolholder block 24 being slidable on a frame of the apparatus 1 in the direction indicated by the arrow F5.

The positioning device 22 furthermore comprises an adjustable member 25 that can be translated by means of a micrometric screw 26 in a direction that is substantially vertical.

The adjustable member 25 comprises a first face 27 arranged substantially vertically and suitable for sliding keeping in

contact with a bar 28 that is integral with the frame of the apparatus 1.

The adjustable member 25 furthermore comprises a second face 29 opposite the first face 27 and tilted in relation to a vertical plane.

The second face 29 is suitable for interacting with an active surface 30, correspondingly tilted in relation to a vertical plane, of the toolholder block 24.

The apparatus 1 furthermore comprises a ~~stop~~an abutting member 31 cooperating with the toolholder block 24 and with the adjustable member 25.

The positioning device 22 furthermore comprises an actuator 32 arranged to transfer the ~~stop~~abutting member 31 between a raised work position, indicated by C in Figure 3, and a lowered rest position, indicated by D in Figure 4.

The ~~stop~~abutting member 31 comprises a yet further first face 33 arranged substantially vertically and suitable for sliding, keeping in contact with a plate 34 connected to the frame of the apparatus 1, when the ~~stop~~abutting member 31 is transferred from the lowered rest position D to the raised work position C, and vice versa.

The ~~stop~~abutting member 31 furthermore comprises a further second face 35 opposite the further first face 33 and tilted in relation to a vertical plane.

The yet further second face 35 is suitable for interacting with a further active surface 36, correspondingly tilted in relation to the vertical, of the toolholder block 24.

The active surface 30 and the further active surface 36 are obtained on opposite sides of the toolholder block 24, the tilt in relation to a vertical plane of the active surface 30 being less than the tilt in relation to a vertical plane of the further active surface 36.

Adjustment of the position of the ~~incision~~etching knife 23 occurs in the manner described below.

By acting on the micrometric screw 26 it is possible to position the adjustable member 25.

Subsequently, the toolholder block 24 is made to slide in the direction of the arrow F5 until the active surface 30 comes to  
 5 abut on the second face 29 of the adjustable member 25.

Also subsequently, the actuator 32 makes the ~~step~~-abutting member 31 interact with the toolholder block 24 in such a way as to press the further second face 35 into contact with the further active surface 36.

10 In this way, the positioning device 22 is kept in an operating configuration, indicated by A in Figure 3, in which the stress to which the ~~incision~~-etching knife 23 is subjected is transmitted only to the adjustable member 25 and to the ~~step~~-abutting member 31 and from the latter to the frame of the  
 15 apparatus 1.

In other words, during operation of the apparatus 1, the micrometric screw 26 is not subjected to mechanical stress that could damage it or even cause its structural failure.

20 The ~~incision~~-etching knife 23, if it is worn, can be approached to the caps 2 to be cut in such a way as to offset the shortening due to the aforementioned wear.

The approach initially occurs by translating the adjustable member 25 in the direction indicated by the arrow F4.

25 Subsequently, also the ~~step~~-abutting member 31 is transferred in the direction of the arrow F4.

The interaction between the further second face 35 and the further tilted surface 36 causes a shift of the toolholder block 24, in the direction of the arrow F5, approaching a cap 2 that has to be cut.

30 The aforementioned shift of the toolholder block 24 continues until the active surface 30 abuts on the second face 29.

In other words, the tilt of the active surface 30 and of the further active surface 36 enable a correspondence between the size of the shift of the adjustable member 25 in the direction

of the arrow F4 and the size of the shift of the toolholder block 24 in the direction of the arrow F5 to be established.

The positioning device 22 furthermore comprises a further actuator 38 arranged to move the toolholder block 24, when the  
 5 | ~~stop-abutting~~ member 31 is in the lowered rest position D.

By actuating the further actuator 38 it is possible to transfer the device 22 from the operating configuration A to a rest configuration, indicated by B in Figure 4, in which ~~teeth~~  
 | ~~means-the cutting means-arrangement~~ 5 is removed from the  
 10 | second operating turntable 4 in such a way as to enable maintenance operations such as monitoring, or replacement of  
 | the ~~incision-etching~~ knife 23.

As shown in Figures 5 and 6, a monitoring device 39 of the  
 | ~~incision-etching~~ knife 24 can be provided suitable for  
 15 | checking the state of wear of the ~~incision-etching~~ knife 23, when the positioning device 22 is in the rest configuration B.

The monitoring device 39 comprises a further camera 40 supported by an arm 41 movable in the direction indicated by the arrow F6 in relation to a carriage 42 to which the arm 41  
 20 | is slidably coupled.

The monitoring device 39 furthermore comprises a guide element 43 on which the carriage 42 can slide in the direction indicated by the arrow F7.

The further actuator 38 furthermore enables the cutting phase  
 25 | to be eliminated in an extremely simple and rapid manner - without having to stop the operation of the apparatus 1 - in processing cycles performed on caps 2 in which the obtaining of the nominal cutting line is not provided for.

Figures 7 to 12 show a positioning device 22a made according to one version and comprising a plate 250 arranged to support  
 30 | the ~~incision-etching~~ knife 23 and sliding, as shown by the arrow F8, on a frame 252 of the apparatus 1 between an advanced tool position, indicated by L in Figure 8, in which a  
 | ~~tooth means-arrangement~~ of the ~~incision-etching~~ knife 23 can

interact with the caps, and a retracted rest position, indicated by M in Figure 7, in which the tooth means arrangement of the incision-etching knife 23 is far from a zone of interaction with the caps.

- 5 To the plate 250 slidably coupled runners 254 are fixed in a manner substantially free of play to guides 253 fixed to the frame 252.

The plate 250 is furthermore centrally provided with an opening 251 comprising a first edge zone 155, that is further  
10 from the incision-etching knife 23, and from a second edge zone 156, nearer the incision-etching knife 23.

At the first edge zone 155 and at an end face 162 of the plate 250 arranged substantially parallel to the first edge zone 155 there are respectively provided a first abutting element 157  
15 and a second abutting element 158, each one of which comprising the head 159 of a screw the ~~shank-stem~~ 160 of which engages in a threaded hole 161 obtained in the thickness of the plate 250.

The first abutting element 157 is projected from the first  
20 edge zone 155 to inside the opening 251, whereas the second abutting element 158 is projected from the end face 162, from the side opposite the first abutting element 157.

The positioning device 22a furthermore comprises a position adjusting means-arrangement 163 positioned inside the opening  
25 251.

The position adjusting means-arrangement 163 comprises a block 164 fixed to the frame 252.

At one end 166 of the block 164 nearest to the first edge zone 155 a further abutting element 165 is fixed having an active  
30 zone 174 arranged to interact with the first abutting element 157, as will be described in greater detail below.

At a further end 167 of the block 164, opposite the end 166 and therefore nearest the second edge zone 156, a ~~stop~~  
stopping element 168 is fixed.

Between the block 164 and the further abutting element 165 a spacer 169 is interposed.

Similarly to what has been disclosed with reference to the first abutting element 157 and to the second abutting element 158, the further abutting element 165 may comprise a further head 170 of a further screw provided with a further ~~shank-stem~~ received in a further threaded hole obtained in the block 164.

The further abutting element 165 can therefore be easily removed from the block 164 to enable the replacement of the spacer 169 with a further spacer having a different thickness in relation to the thickness of the spacer 169.

In this way the distance of the further stop element 165 from the block 164 can be varied and as a result the position of the ~~incision-etching~~ knife 23 can be adjusted, as will be disclosed in greater detail below.

The positioning device 22a furthermore comprises a tightening means-arrangement 171 comprising a tooth 173, rotationally supported on a body 172 that is integral with the frame 252, movable between a locking configuration W1, indicated by a continuous line in Figure 10, in which the tooth 173 interacts with the second abutting element 158, and a release configuration W2, indicated by a broken line in Figure 10, in which the tooth 173 does not interact with the second abutting element 158.

Before starting an operating cycle of the apparatus 1, the ~~incision-etching~~ knife can be positioned in the manner disclosed below.

Starting from the retracted rest position M, the plate 250 is made to slide along the guides 253 until the first abutting element 157 makes contact with the further abutting element 165 and the plate 250 is arranged in the advanced work position L.

When the plate 250 is in the retracted rest position M, the tooth 173 takes on the release configuration W2, in such a way as to enable the plate 250 to run along the guides 253.

The plate 250 can be transferred from the retracted rest position M to the advanced work position L, by an operator acting manually thereupon.

In this way, the final adjustment operations of the apparatus are extremely rapid.

In addition, as the plate 250 can be moved manually, it is possible to obtain an apparatus that has a moderate cost inasmuch as actuating devices arranged to translate the plate 250 and the ~~incision~~-etching knife 23 integral therewith do not need to be installed.

When the plate 250 has reached the advanced work position L, the tooth 173 takes on the locking configuration W1 so as to interact with the second abutting element 158 to prevent sliding of the plate 250 along the guides 253.

In this way, during operation of the apparatus 1, the stress transmitted to the ~~incision~~-etching knife 23 is discharged onto the frame 252 by means of the tooth 173.

When it is necessary to conduct maintenance or replacement operations of the ~~incision~~-etching knife 23, the tooth 173 is again positioned in the release configuration W2, in which it allows the plate 250 to run along the guides 253 to reach the retracted rest position M, in which the second edge zone 156 is placed in contact with the ~~step~~-stopping element 168.

The plate 250 can be taken from the advanced work position L to the retracted rest position M thanks to the manual intervention of an operator, similarly to what has been disclosed above.

When the plate 250 is in the retracted rest position M it is furthermore possible to replace the spacer 169 with a further spacer having a different thickness.



This enables the active zone 174 of the further abutting element 165 to be moved towards to or away from the block 164, in such a way as to regulate the amount of the stroke that the plate 250 accomplishes running along the guides 253 before the first abutting element 157 comes into contact with the active zone 174.

As a result, it is possible to monitor the operating position taken up by the ~~incision-etching~~ knife 23, when the plate 250 with which it is integral is in the advanced work configuration L.

In other words, by replacing the spacer 169 with a further spacer having a suitable thickness, it is possible to obtain an apparatus wherein the distance of the ~~incision-etching~~ knife from the caps to be cut can be adjusted, for example to offset shortening due to wear of the ~~incision-etching~~ knife.

A monitoring device can also be provided that checks the state of wear of the ~~incision-etching~~ knife 23.

As shown in Figures 13 and 14, the apparatus 1 furthermore comprises a pressurized air recovery device 44.

The pressurized air recovery device 44 comprises a conduit 45 connected to, a ~~suction means-device~~ suitable for sucking up the appendages of the casting feedheads that are removed from the caps 2 by means of the cutting device 37 associated with the ~~transfer-transferring~~ turntable 6.

The conduit 45 traverses a filter 46 suitable for separating the aforementioned appendages from the air arranged to convey them.

The conduit 45 terminates inside a manifold 47 connected to a fan arranged to direct the air - by a transfer conduit 49 - to the pneumatic conveying device 8 that supplies the first operating turntable 3.

The pressurized air recovery device 44 comprises a further conduit 50 connected to further suction ~~means-device~~ suitable

for sucking up flashing produced by the interaction between the cutting ~~means-arrangement~~ 5 and the caps 2.

The further conduit 50 traverses a further filter 51 suitable for separating the aforementioned flashing from the air arranged to convey it.

The further conduit 50 terminates inside the manifold 47, in such a way that the air brought by the latter, together with the air conveyed by the conduit 45, provides supplying of the fan 48.

The pressurized air recovery device 44 enables energy consumption to be limited due to a pressurized-air generating means-device inasmuch as air having a pressure greater than atmospheric air is reused rather than being discharged into an external environment.

With reference to Figure 15, the folding ~~means-arrangement~~ 52 is shown, which comprises a plurality of collars 148, each fitted on a respective disc body 55 and sliding on a relative spindle 53 such as to fold the flaps 54 of a cap 2 towards the inside of the cap when the latter is shifted upwards.

The apparatus 1 can furthermore be provided with a cutting means-arrangement -not shown - different from the cutting ~~means-arrangement~~ 5, shown in Figures 4 to 6, and made according to the teachings of International Patent Application WO 99/17911, the contents of which are included here for reference.

In order to provide a folding means-arrangement in WO 99/17911 it is generally sufficient to fit a collar 148 outside the spindle of the cutting ~~means-arrangement~~ disclosed in WO 99/17911.

In particular, this cutting ~~means-arrangement~~ comprises a plurality of jaws having a first end hinged on a respective spindle 53 and a second end with which are associated cutting tools shaped as a circumference ~~areh~~ arc.

The cutting tools have dimensions such as to define, in a configuration in which they are alongside one another, a complete circumference having a diameter substantially corresponding to the external diameter of the caps 2.

- 5 The aforementioned jaws are oscillating, in a direction that is radial in relation to the spindle 53, between a rest position, in which the cutting tools are far from the caps 2, and an operating position, in which the cutting tools tighten on the caps 2 to make a nominal cutting line on the side wall  
10 of the latter.

In this case, the cutting ~~means~~ arrangement is associated with the relative spindle 53 in such a way as to be coaxially arranged in relation to the folding ~~means~~ arrangement 52 and outside them in relation to the spindle 54.

- 15 The folding ~~means~~ arrangement 52 is rotatable around an axis K and is provided with a rotating electric commutator 56 interposed between first electric terminals 57 and second electric terminals 58 suitable for supplying resistances 59 arranged to heat the collars 148.

- 20 In this way, with the apparatus 1 it is possible to very simply hot-fold flaps 54 of caps 2.

With reference to Figure 16, a ~~transfer~~ transferring turntable 6 is shown with which a chamber 60 is associated that defines an environment 61, isolated from the exterior, inside which  
25 the caps 2 can be subjected to preset treatment, such as refrigeration, or heating or treatment in a controlled atmosphere.

Further treatment may comprise irradiation and/or cleaning operations of the caps 2.

- 30 Alternatively, the chamber 60 may be positioned in any zone of the apparatus 1.

In particular, the chamber 60 may be associated with the further ~~transfer~~ transferring turntable 7 rather than with the ~~transfer~~ transferring turntable 6.

As shown in Figure 17, the apparatus 1 comprises a sensor sensing means arrangement 62 comprising a position sensor 63 that detects ~~shifts~~ any shifting of incision-etching knife 23 due to the heat expansion of the latter.

5 The position sensor 63 is connected to the positioning device 22 in such a way as to control the micrometric screw 26 to offset the shift of the incision-etching knife 23.

The ~~sensor-sensing means arrangement~~ 62 may comprise, as an alternative to the position sensor 63, or in addition thereto,  
10 a temperature sensor arranged to detect the temperature of the caps 2.

The temperature sensor is connected to the positioning device, in such a way as to adjust the position of the incision-etching knife 23 taking account of the variations of the  
15 physical characteristics of the caps 2 according to the temperature of the latter. Physical characteristics that are influenced by temperature are, inter alia, the dimensions, mechanical resistance and the friction coefficient of the caps.

20 The ~~sensor-sensing means arrangement~~ 62 may comprise a colour sensor-sensing means device suitable for detecting the colour of the caps 2.

In the prior art different colours are in fact conferred on plastic material having different properties, such as in  
25 particular mechanical resistance.

This is rather important for cutting operations, inasmuch as the cutting ~~means arrangement~~ 5 have to act more energetically on the caps 2 if the latter are made of plastic material provided with greater resistance.

30 The colour ~~sensor-sensing means device~~, therefore, after detecting the colour of the caps 2, on each one of which a nominal cutting line must be obtained, correspondingly ~~control~~ controls the positioning device 22.

The presence of the ~~sensor-sensing means-arrangement~~ 62 and ~~their-the~~ interaction thereof with the positioning device 22, enables remote monitoring of the position of the ~~incision~~ etching knife 23 of the apparatus 1.

5 With reference to Figures 18 to 20, 100 globally indicates an apparatus to fold a fixing promoting means-arrangement of- for fixing caps in synthetic material according to the invention, said fixing promoting ~~means-arrangement~~ being constituted for example by a tamperproof ring.

10 The apparatus comprises a base that rotationally centrally supports a vertical shaft 102 that actuates a rotating turntable 103. At the top of the vertical shaft 102 a substantially tubular body 104a is supported with interposition of rolling bearings 104 on which a top cover  
15 104b is locked fixed coaxially in relation to the base. The rotating turntable 103 is suitable for conveying the caps 2 in synthetic material, each one of which is provided with a respective tamperproof ring 106, the caps 2 are supplied continuously by a conveying meansdevice.

20 According to the invention, the turntable 103 comprises a plurality of receptacles 107 for respective caps 2, angularly spaced at an equal distance from one another and provided with a substantially uniform peripheral distribution of folding ~~means-arrangements~~ 108 articulated according to respective  
25 radial planes, the intersection of which planes being the axis of symmetry H of the cap 2; the folding ~~means-arrangements~~ 108 ~~is-are~~ suitable for rotating from a first substantially retracted angular position outside the perimeter of the tamperproof ring 106 to a second angular position extending in  
30 a centripetal direction in relation to the axis H of the cap to fold the tamperproof ring 106 inside the cap.

The rotating turntable 103 is constituted by a bottom drum 109 to which there is connected at the top, for example by screws 110, a support 111 extending with top arms 111a that are

angularly spaced at an equal distance from one another. The bottom drum 109 has a thicker part 112 with a plurality of through holes 113 having respective axes parallel to those of the shaft 102 in which respective bushes 114 are housed. Each  
 5 arm 111a of the support 111 has a through channel 115 made vertically and aligned on a respective through hole 113 of the thicker part 112.

The cover 104b has an external surface grooved by a ring track 116 with a substantially rectangular transverse section and  
 10 with an appropriate contour.

The apparatus is provided with a plurality of lifting organs 117 suitable for ~~making the translation of~~ translating the caps 2 axially from a bottom inlet ~~supply~~ supplying position to an intermediate position in the receptacles 107, ~~to in~~ which the  
 15 caps 2 are taken, with the respective tamperproof rings 106, in peripheral contact along ~~their~~ the side surface thereof with the folding ~~means~~ arrangements 108 in the first inactive angular position, and from said intermediate position to a top position wherein the folding ~~means~~ arrangements 108 ~~is~~ are  
 20 rotated to the second angular position.

The lifting organs 117 comprise, for each of the caps 2 housed between the respective receptacles 107, a bottom plate 118, possibly supported by a respective trunk 118a, to support a respective cap 2 resting on its flat surface; the plate 118 is  
 25 associated with an actuating ~~means~~ device to lift the cap 2 from the bottom position to the intermediate position and from the intermediate position to the top position.

The lifting organs 117 also comprise, for each receptacle 107, a sleeve 119 fixed coaxially inside the respective bush 114, bearing integrally with the bottom end an annular body 120  
 30 abutting on a respective diameter 21 narrowing. Along the sleeve 119 a collar 122 is furthermore splined substantially in the middle.

Inside the sleeve 119 a ~~shank~~-stem 123 is guided slidably axially that is provided below with a threaded portion along which a foot 124 is threaded that is engageable on the flat surface of the respective cap 2. At the opposite end the ~~shank~~  
 5 | stem 123 is connected elastically, through the interposition of a top contrast spring 125 to a pad 126 engaged slidably in the respective channel 115 of the support 111; the pad 126 is provided laterally with an idle wheel 127 suitable for rolling along the annular track 116 of the cover 104b, such as to  
 10 | determine a preset axial shift of the ~~shank~~-stem 123 in relation to the angular position of the turntable 103 in relation to the cover 104b.

Along the external surface of the sleeve 119 (see figures 19 and 20), particularly below the collar 122, a moving element  
 15 | 128 is slidably guided that carries the folding ~~means~~ arrangements 108 distributed below of the tamperproof ring 106: the moving element 128 is translatable integrally with the cap 2 by means of the lifting organs 117 from the intermediate position to the top position defined previously.

20 | The annular body 120 has, on the bottom face, a uniform distribution of radially arranged projections 129 angularly spaced at an equal distance from one another and having a curved substantially convex contour; this is furthermore affected by a plurality of cylindrical through seats 130 with  
 25 | respective axes that are parallel to those of the ~~shank~~-stem 123.

The moving element 128 is constituted by a coupling 131 with which an annular plate 132 is integral at the bottom that is coaxial to the coupling. The coupling is provided with a  
 30 | plurality of peripherally distributed cylindrical seats 133 having two diameters; along the internal surface of the coupling 131 and substantially in the middle an internal ring 134 is obtained provided with holes 135 with respective axes  
 | parallel to the axis of the ~~shank~~-stem 123 and in which are

respectively locked partially emerging pegs 136 and which slide in the respective through seats 130.

In the bottom portion 137 with a lesser diameter of each of the cylindrical seats 133 a respective rod 138 is inserted,  
 5 axially sliding inside a pair of coaxial bushes 139. Each rod 138 has a substantially flat base 140, whereas the top is provided with a head 141 defining a support surface with a circular crown.

In the top portion 142 of each cylindrical seat 133, with a  
 10 greater diameter, which is threaded for a certain length at the port, a peripheral helical spring 143 is inserted having the bottom edge 143a abutting on the head 141 of the rod 138, and the top end 143b actuated by a disc 144 on which a grub screw 145 acts that is screwed in the seat 133.

15 A bottom spring 146, for example with wire with a rectangular section, is fitted coaxially along the sleeve 119 and has a first bottom end 146a resting on the internal ring 134 of the coupling 131, whereas the top second end 146b stops on the collar 122 splined along the sleeve 119.

20 The annular plate 132 has a plurality of openings 147 angularly spaced at an equal distance from one another for the housing of the respective folding ~~means~~arrangements 108; it defines, along its internal surface, a shoulder 148 suitable for stopping the edge of the cap 2.

25 According to the invention, the folding ~~means~~arrangements 108 ~~comprises~~comprise a plurality of rocker arms 149 rotationally supported on respective pivots 150 each one of which is fitted in a respective opening 147 and is locked with horizontal grub screws 150a with axes arranged in directions substantially  
 30 tangential to the cap 2 (Figure 21).

Each of the rocker arms 149 has a free contact end 151 with the external side surface of the tamperproof ring 106, end provided with a roller 152 suitable for rolling along the respective projection 129 of the annular body 120, so that to



the first inactive angular position of the rocker arm 149 a roller 152 position corresponds that is substantially peripheral to the annular body itself, whereas to the second angular position a roller position of the roller 152 corresponds that is substantially central and extended inside the cap 2 to fold the tamperproof ring 106 inside.

The free end 151 of each rocker arm 149 is substantially shaped as a fork with the respective prongs 153 suitable for rotationally supporting the roller 152. The transverse distance between the prongs 153 is substantially greater than the greater thickness of the respective projection 129 of the annular body 120, to enable rotation of the rocker arm 149 without interference.

Each rocker arm 149 also has an end portion 154 opposite the respective free end 151, with concave surface, engaged against the base 140 of the respective rod 138. The rod 138, through the action of the peripheral spring 143, thus enables, with the cap 2 and the coupling 132 in the intermediate position the roller 152 to be placed in the peripheral position of the annular body 120; the coupling of the flat base 140 of the rod 138 with the concave surface of the terminal portion 154 ensures that the rod 138 is subjected to prevalently axial stress.

The operation of the apparatus according to the invention is as follows.

The continuously supplied caps 2 are each deposited on a respective plate 118 lying on the respective flat surface in the bottom position of the lifting organs 117. Each ~~shank-stem~~ 123, actuated by rolling of the respective wheel 127 in the track 116 is made to descend until the foot 124 comes to engage in the flat surface of the cap 2.

Each cap 2, locked between the respective plate 118 and the foot 124, is then lifted from the bottom position until it reaches the intermediate position (Figure 19), where it is

inserted in the respective receptacle 107 with the edge stopping on the shoulder 148 of the annular plate 132. The presence of the top spring 125 associated with the ~~shank~~-stem 123 enables compensation of even slight dimensional differences between the different caps 2, due to manufacturing imperfections.

The cap 2 continues its ascent stroke (which occurs constantly without interruptions), reaching the top position (Figure 20), thereby also determining the corresponding upward transfer of the moving element 128. In particular, the coupling 131 together with the annular plate 132 perform a vertical stroke, elastically opposed by the bottom spring 146: this upward stroke causes each roller 152 to roll along the respective projection 129 in a direction that is centripetal from the peripheral position to the central position. In this way, each roller 152 exerts centripetal pressure on the external lateral surface of the tamperproof ring 106, folding it inside the cap 2.

At the same time the terminal portion 154 of each rocker arm 149, following the rotation of the latter from the first inactive angular position to the second angular position, transmits a force that is substantially axial to the relative rod 138: the rod 138 thus transfers upwards, compressing the peripheral spring 143.

After the tamperproof ring 106 has been folded, the cap 2 is lowered until it again reaches the bottom position, thanks to the simultaneous downwards transfer of the ~~shank~~-stem 123 (that facilitates expulsion of the cap 2 from the receptacle 107) and of the plate 118. To this shift also corresponds the descent of the moving element 128 to the corresponding initial position (corresponding to the intermediate position of the cap 2), caused by the bottom spring 146; there is also the axial downward transfer of the rods 138, caused by the peripheral springs 143 with the rocker arms 149 that

correspondingly rotate, thereby reaching the first angular position.

5 The apparatus according to the invention enables the tamperproof ring 106 to be folded by folding means arrangements 108 that act in directions that are substantially radial in relation to the axis of the cap 2, thereby preventing the cap from being subjected to excessive stress that is a frequent cause of undesired plastic deformation.

10 Moreover, the apparatus is highly versatile and can easily be set up and adapted to the changing shapes and dimensions of the caps.